


INPUT WASH1 WASH2 RINSE DRY OUTPUT



SPECIFICATION	
Model	SLM-WF2DS-ES
Power	380/220V, 3PH, 12.75 kw
Size	6,200L x 1,210W x 1,800H
Capacity	Dish 7,800ea/hr, Tray 2,600ea/hr
Conveyor Speed	1.6 m/min
Drive Motor	0.75 kw
Pump Motor	Wash 4.5 kw x 2 Rinse -
Blower Motor	E/Save 0.75 kw x 2 Dry 0.75 kw x 2
Temperature	Wash 60 ~ 65 °C
	Rinse 81 ~ 92 °C
Pipe Conn.	Water 20A(1.5 kg/cm ²)
	Steam 32A(2.5 kg/cm ²)
	Drain 40A
Wash Tank	150L x 2
Using Water	20L /min

29	Fan Motor	0.75kw	
28	Condenser	Fin type	
27	Conveyor Motor	0.75kw	
26	Stopper	sus304	
25	Sprocket	Plastic	
24	Steam Booster	Pipe Weld'g	
23	Reflector	sus304	
22	Fan Motor	0.75kw	
21	Dry Coil	Steam type	
20	Dry Nozzle	sus304	
19	Controller	PCB/LCD	
18	Control Box	sus304	
17	Spray Nozzle	sus304	
16	Level Sensor	sus304	
15	Overflow Pipe	sus304	
14	Drain Pipe	40A	
13	Pump Motor	6HP	
12	Wash Nozzle	Plastic	
11	Door Holder	sus304	
10	Door Spring	Plate spring	
9	Adjuster	M16 Bolt	
8	Strainer	#2.5 Punch	
7	Door	sus304	
6	Exhaust	sus304	
5	E.M.S	Push Button	
4	Curtain	P.E	
3	Flight Conveyor	Nylon/ sus	
2	Tension Unit	sus304,M16	
1	Guide Plate	sus304	

Title SLM - WF2DS-ES			
Name	Outside view	Drawn by xizix	
Scale	1/1	Date 10. 6.25	Checked by
SJM SHIN JIN MASTER CO.,LTD		Approved by	Dwg. No